



CONVEYOR BELT SKIRTING

Polyurethane Skirting If you are after longer product life and less maintenance then try our Premium Grade Polyurethane Skirting. 70 shore "A" poly skirt has up to 8-10 times the wear life of natural black skirting rubber. It also has greater strength properties, more durability and the 35 deg bevelled edge provides a better seal.

Black Natural Skirting Rubber (65 shore 'A' & tensile strength 3MPA), the traditional product of choice widely used in the quarry, mining and material handling industries.

Orange Skirting Rubber (40 shore 'A' & tensile strength 16MPA) has better abrasion resistant properties with up to 3-5 times the wear life of black natural skirting rubber and is a premium product.



PRODUCT CODE	DESCRIPTION
SKB10-150-15	10mm X 150mm X 15m
SKB12-200-15	12mm X 200mm X 15m
SKO10-150-10	10mm X 150mm X 10m
SKO12-200-10	10mm x 200mm x 10m
SKO12-300-10	10mm x 300mm x 10m
SKP10-100-10	10mm x 100mm x 10m
SKP10-150-10	10mm x 150mm x 10m
SKP10-150-15	10mm x 150mm x 15m
SKP12-200-10	12mm x 200mm x 10m
SKP12-200-15	12mm x 200mm x 15m
SKP12-300-10	12mm x 300mm x 10m

SKB - Black Rubber
SKO - Orange Rubber
SKP - Polyurethane