

Advanced Engineering Group supply FLOMAX harp/piano wire screen cloths to suit all types and brands of screening plants. AEG can supply almost any specification required up to 3300mm over hooks and 1830mm wide. Apertures from 1mm to 20mm and Wire Diameters 0.65mm to 3mm in steel or stainless steel.

## **PROFILES**







Plastic Square

Plastic Round

Steel Round

## **HOOK STYLES**







## FloMax Screen Duty Descriptions

**Light Duty-** Use for screening wet, sticky materials where screening is very difficult or for very high productivity

**Standard Duty-** Use for screening damp materials where screening is difficult or for good productivity

**Heavy Duty-** Use for screening dry, abrasive materials. Will give lower productivity

**Extra Heavy Duty-** Used for screening very abrasive, very dry free flowing materials but will give lower productivity.

Thicker wires give better screen life but reduce productivity.

Thinner wires give less screen life but increase productivity.

		Standard	Heavy	Extra Heavy
Aperture	Standard	Heavy	Duty	Duty
1mm	0.65mm			
2mm	0.65mm	0.8mm	1.0mm	1.2mm
3mm	0.8mm	1.0mm	1.2mm	1.4mm, 1.6mm
4mm	1.0mm	1.2mm	1.4mm	1.6mm, 1.8mm
5mm	1.0mm, 1.2mm	1.4mm	1.6mm	1.8mm, 2.0mm
6mm	1.2mm, 1.4mm	1.6mm	1.8mm	2.0mm, 2.5mm
7mm	1.2mm, 1.4mm	1.6mm	1.8mm	2.0mm, 2.5mm
8mm	1.4mm, 1.6mm	1.8mm	2.0mm	2.5mm, 3.0mm
10mm	1.4mm, 1.6mm	1.8mm	2.0mm	2.5mm, 3.0mm
12mm	1.6mm	1.8mm	2.0mm	2.5mm, 3.0mm
14mm	1.8mm	2.0mm	2.5mm	3.0mm
16mm	1.8mm	2.0mm	2.5mm	3.0mm
18mm	1.8mm	2.0mm	2.5mm	3.0mm
20mm	1.8mm	2.0mm	2.5mm	3.0mm