



VIBREX SCREENS SPECIFICATIONS

VIBREX screens composed of individual wires that vibrate independently at different frequencies to help prevent material accumulating between the wires and allowing the self-cleaning effect.

Aperture	Wire Diameters (Poly Screens)			
2.50	1.25	1.60		
2.75	1.60	2.00		
3.15	1.25	1.60	2.00	
3.50	1.25	1.60	2.00	
4.00	1.60	2.00	2.50	2.80
4.50	1.60	2.00	2.50	2.80
5.00	1.60	2.00	2.50	3.15
5.60	1.60	2.00		
6.00	2.00	2.50	2.80	3.15
6.30	2.00	2.50	2.80	3.15
7.10	2.00	2.50	3.15	
8.00	2.00	2.50	3.15	
9.00	2.50	3.15		
9.50	2.50	3.15	4.00	
10.00	2.50	3.15	4.00	
10.50	4.00			
11.20	2.00	2.50	3.15	4.00
12.00	2.50	3.15	4.00	5.00
12.70	3.15	4.00		
13.20	2.50	3.15	4.00	
14.00	2.50	3.15	4.00	5.00
15.00	3.15	4.00	5.00	
16.00	3.15	4.00	5.00	
17.00	3.15	4.00	5.00	
18.00	3.15	4.00		
19.00	3.15	4.00		
20.00	4.00	5.00	6.30	
22.40	4.00	5.00	6.30	
25.00	4.00	5.00	6.30	
28.00	4.00	5.00	5.60	6.30
30.00	6.30			
31.50	5.00	6.30		

BOLD – NZ MADE

* Custom specifications are available on request

Christchurch
03 384 9595
sales@aeg-group.nz
www.aeg-group.nz

For more information on our products and services visit our website at: